

Multifunction B&W

RICOH
IM 350F
IM 430F
IM 430Fb

✓ Copier ✓ Printer ✓ Facsimile ✓ Scanner



Smart office assistant

Harnessing the power of the cloud, these smart multifunction printers automate everyday document processes, leaving you free to focus on your core business activities.

Intelligent workflow tools:

- Intuitive user interface
- Ricoh Smart apps
- Cloud-share services
- Smartphone connection

Ricoh's super-sized 10.1 inch Smart Operation Panel is host to a suite of intelligent workflow tools. Pre-installed Smart apps, such as ID Card Copy, automate time-consuming processes. More applications can be installed on demand. It is easy to print from and scan to smartphones and tablets, and critical documents can be scanned in color directly to DropBox™ or Sharepoint™.

Simply more productive:

- 37 & 45 ppm print speeds (letter)
- 14 - 68 lb. Bond (52 - 256 gsm)
- Large paper capacity
- Offline stapler option



To save time, double-sided originals are scanned in a single pass. The first immaculate 1200 dpi print is ready in under 6 seconds. Multipage documents are produced at speeds of 37 or 45 pages per minute and can be quickly collated using the Offline Stapler option. The optional High Capacity Paper Trays further enhance productivity. It is easy to print onto envelopes and labels. And, with the printer switching from one tray to another, you need never run out of paper.

Despite their advanced functionality, Ricoh's new multifunction printers are surprisingly easy to set up and support. With their compact design and quiet operation, they are a perfect fit for every office. Ricoh's installation wizard simplifies setup. To safeguard information, they support tap and go authentication and confidential documents can be securely locked, pending release. Clever energy saving features reduce power consumption and contribute to a low total cost of ownership.

A friendly and affordable solution:

- Space saving design
- Secure authentication
- Confidential printing



RICOH IM 350F/IM 430F/IM 430Fb

MAIN SPECIFICATIONS

	RICOH IM 350F	RICOH IM 430F	RICOH IM 430Fb
GENERAL			
Warm-up time	Quick Mode: 23 seconds Without Quick Mode: Less than 47.4 seconds	Quick Mode: 24 seconds Without Quick Mode: Less than 49.3 seconds	Quick Mode: 24 seconds Without Quick Mode: Less than 49.3 seconds
First output speed: B/W	5.4 seconds (A4 / LT SEF)	4.5 seconds (A4 / LT SEF)	4.5 seconds (A4 / LT SEF)
Continuous output speed	37 ppm	45 ppm	45 ppm
Memory: standard	2 GB		
Memory: maximum	2 GB		
HDD: standard	320 GB		
HDD: maximum	320 GB		
SPDF capacity	50 sheets		
Weight	67.24 lbs. (30.5 kg)		
Dimensions: W x D x H	18.7" x 17.4" x 20.1" (476 x 442 x 510 mm)		
Power source	120-127V/12A 60Hz		
COPIER (STANDARD)			
Multiple copying	Up to 999 copies		
Copy resolution: maximum	600 x 600 dpi		
Zoom	From 25% to 400% in 1% steps		
PRINTER (STANDARD)			
CPU	Intel Atom Processor Bay Trail 1.46GHz		
Printer language: standard	PCL5e, PCL6, PostScript 3 (emulation), PDF direct (emulation)		
Printer language: option	Genuine Adobe® PostScript® 3™, IPDS, PDF Direct from Adobe®		
Print resolution: maximum	1,200 x 1,200 dpi		
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host 2.0		
Network interface: option	Wireless LAN (IEEE 802.11a/b/g/n), Additional NIC (2nd port), Extended USB Board, File Format Converter		
Mobile printing capability	Apple AirPrint™, Mopria, Google Cloud Print, NFC, Ricoh Smart Device Connector		
Network protocol	TCP/IP (IP v4, IP v6)		
Windows® environments	Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012, Windows® Server 2012R2, Windows® Server 2016		
Mac OS environments	Macintosh OS X v10.10 or later		
UNIX environments	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux, IBM® AIX, Citrix XenApp		
SAP® environments	SAP® R/3®, SAP® S/4®		
Other supported environments	NDPS Gateway, AS/400® using OS/400 Host Print Transform, IBM iSeries		
SCANNER (STANDARD)			
Scanning: B/W	45.7 ipm		
Scanning: full color	45.7 ipm		
Resolution: maximum	600 dpi		
Compression method	TIFF (MH, MR, MMR, JBIG2), Grayscale		
File formats	Single Page TIFF, Single page JPEG, Single page PDF, Single page High compression PDF, Single page PDF/A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF/A		
Scan modes	E-mail, Folder, USB, SD Card		
FAX (STANDARD)			
Circuit	PSTN, PBX		
Transmission speed	2 seconds (200x100 dpi, JBIG, ITUT #1 chart TTI off, memory transmission)		
Modem speed: maximum	33.6 Kbps		
Resolution: standard	8x7.7 line per mm, 200x200 dpi		
Compression method	MH, MR, MMR, JBIG		
Scanning speed	28 spm		
Memory: standard	4 MB (Approx. 320 pages)		
Memory: maximum	4 MB (Approx. 320 pages)		
PAPER HANDLING			
Recommended paper size	Standard paper tray(s): 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6-B5) Optional paper tray(s): 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6-B5) Bypass tray: 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6-B5) Custom Sizes - Width: 2.36" - 8.5" (60 - 216 mm), Length: 5.0" - 35.43" (127 - 900 mm)		
Paper input: standard	500 sheets		
Paper input: maximum	2,100 sheets		
Paper output: standard	250 sheets		
Paper weight	Trays: 14 - 58 lb. Bond (52 - 220 g/m²) Bypass: 14 - 68 lb. Bond (52 - 256 g/m²) Duplex: 14 - 43 lb. Bond (52 - 162 g/m²)		
Paper types	Plain, Recycled, Special, Colored, Letterhead, Cardstock, Pre-printed, Bond, Coated, Envelope, Label, OHP		

RICOH IM 350F/IM 430F/IM 430Fb

MAIN SPECIFICATIONS

RICOH IM 350F

RICOH IM 430F

RICOH IM 430Fb

ECOLOGY

Power consumption: Maximum (kW)	Less than 1,380 W		
Power consumption: operation	566 W	628 W	628 W
Power consumption: ready	91 W		
Power consumption: sleep	0.7 W	0.74 W	0.74 W
TEC ¹	0.46 kWh	0.57 kWh	0.57 kWh
ENERGY STAR®	Certified		
EPEAT®	Gold Rated*		
	* EPEAT Gold rating is applicable only in the USA.		

OUTPUT TRAYS

1 x 250-sheet Paper Tray (PB 1110)	Paper size: 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6); Paper weight: 14-58 lb. Bond (52-220 g/m²)
1 x 500-sheet Paper Tray (PB 1120)	Paper size: 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6-B5); Paper weight: 14-58 lb. Bond (52-220 g/m²)

OTHER OPTIONS

IPDS Unit Type M34, Offline Stapler Type M34, PostScript 3 Unit Type M34, IEEE 802.11 Interface Unit Type M24, USB Device Server Option Type M19A, File Format Converter Type M19, OCR Unit Type M13, Page Keeper Type M28, Extended USB Board Type M19, Medium Cabinet Type P, Tall Cabinet Type Q, Caster Table Type M34, Optional Counter Interface Unit Type M12, NFC Card Reader Type M27

CONSUMABLE

	Starter Supplies	Yield (CTN)
RICOH IM 350F		
Print Cartridge IM 350	14,000	14,000
Refill Staple Type M34		5,000
RICOH IM 430F		
Print Cartridge IM 430	17,400	17,400
Refill Staple Type M34		5,000
RICOH IM 430Fb		
Print Cartridge P 501H		14,000
Print Cartridge P 501L	6,000	3,000
Refill Staple Type M34		5,000
Drum Unit P 501		40,000
Maintenance Kit P 501		120,000

¹ TEC value is measured based on the ENERGY STAR Ver. 3.0 test method.

Some options may not be available at the time of market release.

Specifications are subject to change without notice.

For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.

Some features may require additional options and/or charges.

Ricoh USA, Inc.

300 Eagleview Boulevard
Exton, PA 19341



1-800-63-RICOH



www.ricoh-usa.com

RICOH
imagine. change.

Ricoh USA, Inc., 300 Eagleview Boulevard, Exton, PA 19341, 1-800-63-RICOH
©2019. Ricoh USA, Inc. All rights reserved. Ricoh® and the Ricoh logo are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners. The content of this document, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them.

R4031-3